

nmcli

Смотрим сетевые устройства:

```
# nmcli dev
```

DEVICE	TYPE	STATE	CONNECTION
enp64s0	ethernet	подключено	enp64s0
enp5s9	ethernet	подключено	enp5s9
lo	loopback	без управления	--

```
# nmcli con show
```

NAME	UUID	TYPE
enp5s9	1454cfa8-305a-446e-a257-8d8e6a884c05	
ethernet enp5s9		
enp64s0	f1963841-564a-4e83-8417-89279a1ce0cd	
ethernet enp64s0		
Wired connection 1	e21c76c3-554e-3743-9c72-feb52fb1972a	
ethernet --		

Добавить адрес

```
# nmcli con add con-name enp5s9 ifname enp5s9 type ethernet  
ip4 10.10.5.1/24 gw4 10.10.5.1
```

Создать VLAN

```
# nmcli con del eth0
```

To create the two vlans on the eth0 network interface, type:

```
# nmcli con add type vlan con-name vlan10 dev eth0 id 10
```

To check the new configuration, type:

```
# nmcli con show
```

Configure the network interfaces

```
# nmcli con mod vlan5 ipv4.addresses 10.10.5.1/24 # nmcli con  
mod vlan5 ipv4.gateway 10.10.5.1 # nmcli con mod vlan5  
ipv4.method manual # nmcli con up vlan5
```

RHEL7: How to configure vlans.